

SEA-LADY 5150 BHP AHTS



Principal Particulars		Machinery		
Call Sign IMO Number	9LU2455 9337561	Main Engine	2 × 2575 BHP CATERPILLAR INC. 3516B-HD	
Year Of Built	2005	Main Generator	3 × 315 KW CAT	
Port of Registry	Freetown	Emergency Generator	1 × 52 KW CAT	
Builder	Guangzhou Southern Ship building Co Ltd - Guangzhou	Bow Thruster	1 × 430 BHP tunnel (5T)	
		Steering Gear	2 × 35 degree- 6 T-M	
Flag	Republic of Sierra Leone	Propulsion	2 × CPP with Kort Nozzle	
Class	RINA	Rudders	2 X Conventional Split	
Notation	ABS, Class 1 Hull +Mach, Supply Unrestricted Navigation FIFI 1 + Self protection			
Dimension		Performance		
Length Overall	58.7 M	Bollard Pull	60 T	
Depth Moulded	5.5 M	Speed - Average/ Fuel Con-	10 Knots @ 6 T/Day	
Beam, moulded	14.6 M	sumption		
Full Load Draft	4.8 M	Speed- Maximum / Fuel Consumption	13 Knots @ 7 T/Day	
		Fuel Consumption in Port	0.5 M/T	





Towing Equipment		Navigation &	Communication
Anchor Handling	1000 M \times 56 MM of wire rope, lower drum	VHF (semi-duplex)	2 × GMDSS Furuno
First layer: Low Speed	150 T @ 6 M/Min	EPRI	1
Mid Speed	71 T @12 M/Min	VHF Radio	$3 \times GMDSS$ - portable radio (2-way portable)
High Speed	23 T @ 36 M/Min	Furuno Imers sat-c	2
Remote control	From aft control stand in Wheelhouse	Navtex receiver	1 × Furuno Weather fax
Towing Pin	1set hydraulic operated type SWL 200T	x-Band Radar	1 × Furuno Radar
Shark Jaw	1set hydraulic operated type SWL 200T	Echo Sounder	1 × Furuno Echo Sounder receiver
Tow Drum	1000 M \times 56 MM Wire rope, upper drum	GPS Plotter	1 × Furuno
Chains	440 M \times 40 MM Grade U2 stud link chain	Gyrocompass	1
Braking Capacity	200 T	speed log	1 x Furuno
Windlass	9T @12 M/Min for 38mm Ø chain w/2		
Cable lifers	@ 2 warping drums		
Bow Anchors	High-holding type anchors Bow Anchors 1.300 KG P&S		
Tugger Winches	2×10T @ 15M /Mins		
Capstans	2 × 5T @15M/ Mins		
Towing Bollard	Forward SWL80T		
Stern Roller	1.6M \acute{o} and 5M lgth w/SWL200T Windlass:		
Braking Capacity Windlass Cable lifers Bow Anchors Tugger Winches Capstans Towing Bollard	200 T 9T @12 M/Min for 38mm Ø chain w/2 @ 2 warping drums High-holding type anchors Bow Anchors 1.300 KG P&S 2 ×10T @ 15M /Mins 2 × 5T @15M/ Mins Forward SWL80T 1.6M Ø and5M lgth w/SWL200T Windlass:	,	1 x Furuno

Fire Fighting Equip	ment	Cargo Capaci	ties
EXTERNAL		Clear Deck Area	375 M ²
FIFI 1		Deck Strength	7.0 T/M ²
$2 \times 1200 \text{ M}^3 / \text{ hr Pumps } 2 \times 1200 \text{ m}^3 / hr Pumps $	$2 \times 1200 \text{ M}^3 / \text{ hr Pumps } 2 \times 1200 \text{ M}^3 / \text{ hr Monitor (with remote control)}$		476 M³ @100%
Emergency fire Pump		Potable Water	200 M ³ @100%
INTERNAL		Drill Water	400 M³ @100%
CO2 System in Engine Roor	m	Mud	225 M ³ @100%
Fire Detection & Alarm Syst	tem throughout vessel	Liquid Mud	255 M³ @100%
Rescue Zone	Port & Starboard Side	Dry Bulk	4 × 1.650 ft3
Oily Water Separator	$1 \times 1 \text{ M}^3/\text{hr MARPOL standard}$		
Water Maker	1 × 5 T/Day Reverse Osmosis		
Sewerage Treatment Plant	1×40 men per day		
Accommodation			
Berth cabins	1 X 2		
Berth cabins	2 X 4		

Accommodation		
Berth cabins	1 X 2	
Berth cabins	2 X 4	
Berth cabins	4 X 8	
Berth cabins	1 X 1	
Crew	8	
Passengers	34	
Total	42	







